

**BLK 2.16**



**BLK 16.2**



**BLK 13.2**



**BLK 10.2**



**BLK W16**



**BLK T25**



## HIGHLIGHTS

- Solid steel basket including additional voice-coil ventilation
- Polypropylene cone
- Long excursion rubber surround
- Silk tweeter with neodymium magnet

- Mac Audio design magnet protection cover
- Suspension and magnetic field optimized with KLIPPEL® measurement system
- Solid hexagon protection cover with aluminium diamond-cut logo
- External XO including PTC tweeter protection circuit (BLK 2.16 only)

SPECIFICATIONS	BLK 2.16	BLK 16.2	BLK 13.2	BLK 10.2	BLK W16	BLK T25
Principle	2-way	2-way	2-way	2-way	2-way	2-way
System	compo	coaxial	coaxial	coaxial	coaxial	coaxial
Power handling RMS/max. (W)	100/300	100/300	80/250	60/220	100/300	50/100
Impedance (Ω)	4	4	4	4	4	4
Frequency response (Hz)	30 - 25 000	30 - 23 000	35 - 23 000	40 - 23 000	30 - 6 000	3500 - 25 000
Crossover frequencies (Hz)	4 000	4 000	4 000	4 500	–	4 000
SPL (dB)	90	90	90	89	90	90
DIN-Ø (mm)	165 W/54 T	165	152	128	165	54
Cutting Out (mm)	144 W/48 T	144	112	94	144	48
Mounting depth (mm)	63 W/20 T	65	52	52	63	20
Art.No.	110 3766	110 3764	110 3762	110 3760	110 3769	110 3768
EAN.	40 23037 03760 9	40 23037 03764 7	40 23037 03762 3	40 23037 03760 9	40 23037 03769 2	40 23037 03768 5